

Valid from 01.07.2016


Copyright by Dehler Yachts. All specifications and prices are preliminary and can be changed without prior warning. Above specifications are non-contractual.
D29/01072016/A



TECHNICAL DATA


LOA	8.75 m / 28'71"
Hull length	8.75 m / 28'71"
LWL	8.00 m / 26'24"
Beam	2.99 m / 9'81"
Draught	
Standard	1.58 m / 5'18"
Competition	1.80 m / 5'91"
Shallow	1.22 m / 4'00"
Displacement	
Standard	3.00 t / 6,614 lbs
Competition	2.85 t / 6,283 lbs
Shallow	3.15 t / 6,945 lbs
Ballast	
Standard	1.12 t / 2,469 lbs
Competition	0.97 t / 2,138 lbs
Shallow	1.27 t / 2,800 lbs
Engine	Diesel approx. 8.6 kW / 11.8 HP
Fresh water	approx. 100 l
Fuel tank	approx. 60 l
CE Certificate	Class B
Mast above WL	14.05 m / 46'09"
Total sail area	43.00 m ² / 463 sq ft
Main sail	26.00 m ² / 280 sq ft
Furling Jib 105%	17.00 m ² / 183 sq ft
Spinnaker	58.30 m ² / 627 sq ft
Gennaker	58.10 m ² / 625 sq ft
Rig	I 11.25 m / 36'11" J 3.15 m / 10'4" P 11.00 m / 36'1" E 4.00 m / 13'2"
Design	judel/vrolijk & co.
Interior	Dehler

DECK LAYOUT



INTERIOR LAYOUT

STANDARD



HULL & DECK

HULL

- GRP hand laid construction
- Supporting bulkheads bonded to the hull
- Construction of hydrolyses proofed polyester resin, vinylester in first layer and roving fabrics
- Guardrail in aluminium for hull protection
- Internally laminate partly sealed with topcoat
- Colour white with blue waterline striping

DECK

- GRP hand laid construction with end grain balsa core for strength and isolation
- Aluminium reinforcements laminated/glued inside for all fittings
- Non-slip surface moulded deck area
- Self draining anchor locker
- Colour white

KEEL & RUDDER

KEEL

- Cast iron L-keel with low centre of gravity
- Stainless steel keel bolts

RUDDER

- Tiller steering system
- Elliptical balanced rudder
- Seawater resistant rudder shaft with stabilising framework
- Self aligning rudder bearings

COCKPIT

- Large cockpit locker on starboard
- Ergonomic, self draining, with integrated non slip surface

DECK EQUIPMENT

- 2 openable deck hatches, saloon and fwd cabin
- 6 side windows, 4 openable
- Sliding hatch at companionway
- 4 mooring cleats
- Stainless steel open bow pulpit
- Stainless steel push pits

- Safety boarding ladder
- Stainless steel handrails on coach roof
- Genoa tracks
- Halyard and sheet winches Lewmar 30 Race, self tailing, on coach roof
- Halyard stoppers on coach roof
- Guide rollers at mast foot
- Dehler patented entrance closing system at companionway
- 1 winch handle
- Manual bilge pump
- Compass mounted over companionway

ENGINE & ELECTRONICS

ENGINE

- Diesel approx. 8.6 kW / 11.8 HP, sail drive with 2 blade folding propeller
- Fuel tank, approx. 60 litres

ELECTRONIC

- Starter battery AGM 12V / 90 Ah
- Consumer battery AGM 12V / 90 Ah
- Main switch for battery
- Control panel with automatic circuit breakers
- Electric bilge pump 12V

LIGHTING

- Interior light in, fwd cabin, galley, salon, head and aft cabin
- Navigation light (LED) and steaming light

NAVIGATION

- Switch panel for electrics

WATER

- Electric fresh water pump

INTERIOR & ACCOMODATION

FORWARD CABIN

- Convenient double berth with storage below

SALOON

- All joinery and panels in mahogany satin finish
- Solid frame woodwork with smooth surface

- Ceiling inner liner in off white
- Alongside sofas on port and starboard
- Detachable backrests
- Salon table with foldable sides

AFT CABIN

- Roomy aft cabin with double berth, wardrobe and cupboard
- Storage space below berth

GALLEY

- Port side functional galley
- Sink with water tap
- Lockers for pots and pans
- 2-burner gas oven

HEAD

- Spacious head with marine toilet
- Holding tank with deck extraction
- Wash basin with water tap

DECK EQUIPMENT

- Filler nozzles for water and fuel

RIGG & SAILS

RIGG

- 9/10 aluminium keel stepped tapered mast
- 2 pairs of spreaders
- Aluminium boom
- Boom vang, rigid
- Backstay, adjustable
- Halyards for main and jib in dyneema
- Main sheet and jib sheets
- Dehler quick reefing system
- Furling system for jib

SAILS

- Elvström FCL triradial cut performance main sail, with 2 reefs, 2 full and 2 short battens and Selden MDS sliders
- Elvström FCL triradial performance jib, 110%